

日立ポンプ機種選定早見表

種類	型式		吸上高さ(m) ←					→ 押上高さ(m)					銘板表示揚水量 (L/分)	同時使用 水栓数の 目安(個)
		ジェット型式	40	30	20	10	0	10	20	30	0	50		
浅井戸用 自動ポンプ	WT-P125X					8		14			22			2~3
	WT-P200X・WT-K200X					8		18		26	28			3~4
	WT-P300X					7		18		26	33			3~4
	WT-P400X					8		23		30	42			4
	WT-K750X					7		23		30	64			6
浅井戸 加压給水用 自動ブラダ式 ポンプ	WM-P150X					8		17		21	22			2~3
	WM-P250X					8		23		29	28			3~4
	WM-P400X					8		26		32	42			4~5
	WM-K750X					8		26		32	51		70	5~7
浅深両用 自動ポンプ	CT-P150X	J15-7X				6		10			24*			2
		J15-12X			12		10				16.5			1~2
	CT-P250X CT-K250X	J25-7X				6		15			37*			3~4
		J25-12X			12		15				29			3
		J25-24X	24		15						11			1
	CT-P400X	J40-7X				6		16			50*			5
		J40-12X			12		16				44			4
		J40-24X	24		16						39			3~4
		J75-24X	24		16						18			2
	CT-P600X	J75-35X	30		16						12			1
		J75-7X				6		16			55*			5~6
		J75-12X			12		16				50			5
		J75-24X	24		16						45			4~5
	CT-K750X	J75-35X	35		16						24			2
		J75-7X				6		16			70*			7
		J75-12X			12		16				66			6~7
J75-24X		24		16						52			5	
浅深両用 自動ブラダ式ポンプ	CM-P250X	J25-7X				7		15			29			3
		J25-12X			12		15				25			2~3
		J25-24X	24		15						11			1
	CM-P400X	J40-7X				7		18			44			4
		J40-12X			12		18				39			4
		J75-24X	24		18						18			2
	CM-P600X	J75-35X	30		18						12			1
		J75-7X				7		18			50			5
		J75-12X			12		18				45			4~5
	CM-K750X	J75-24X	24		18						24			2
		J75-35X	35		18						12			1
		J75-7X				7		21			66			6~7
J75-12X				12		21				52			5	
深井戸用 自動 水中ポンプ	SFM-P450X		30				15			32 (50Hz)			4	
	SFM-P600X		40				15			39 (60Hz)			3	
	SFM-K750X		42				15			26 (50Hz)			3	
										30 (60Hz)			4	
										39 (50Hz)			4	
										41 (60Hz)				

*は吸上高さ6m、全揚程12m時の給水量(参考値)です。